

# EVOline® Port



# EVOline® Port



reddot design award

With EVOline Port sockets and cables simply disappear.

Typically just the collar and cover of the Port are visible on the work surface — with optional illumination by energy saving LEDs in blue, red, green, or white.

A light pull-up motion lets the high-quality aluminum body appear from below and subsequently a push-down motion lets it disappear below the surface together even with attached plugs. The movable cover creates enough space for the cables.


EVOline Port was awarded the "red dot design award".













Description Picture Specification Order number

## **EVOline Port**

Aluminium housing, silver anodised. For work surface with thickness up to 50 mm.

Mounting hole ø 102 mm.

Two sockets, VDE-compliant, 60°, 16 A, contact-protected.

Fixed supply cable 3.0 m with angled plug.



rocking cover and collar made of silver lacquered plastic

1593 1000 3300

rocking cover and collar made of black lacquered plastic

1593 1000 5200

rocking cover made of solid stainless steel in CD design, collar made of plastic, lacquered in stainless steel optics

1593 1003 1100

rocking cover made of solid stainless steel in CD design.
Collar made of plastic, lacquered in stainless steel optics. NIGHTLIGHT effect by blue LEDs under rocking cover with illuminated ON/OFF switch

1593 1003 1200

# **EVOline Port**

Aluminium housing, silver anodised. For work surface with thickness up to 50 mm.

Mounting hole ø 102 mm.
Three sockets, VDE-compliant, 60°, 16 A, contact-protected.
Fixed supply cable 3.0 m with angled plug.



rocking cover and collar made of silver lacquered plastic

1593 1000 0100

rocking cover and collar made of black lacquered plastic

1593 1000 5000

rocking cover made of solid stainless steel in CD design, collar made of plastic, lacquered in stainless steel optics

1593 1002 1600

rocking cover made of solid stainless steel in CD design. Collar made of plastic, lacquered in stainless steel optics. NIGHTLIGHT effect by blue LEDs under rocking cover with illuminated ON/OFF switch

1593 1003 1300

rocking cover made of silver lacquered plastic, collar made of grey plastic

1593 1000 0600

# **EVOline Port CUISINE**

Aluminium housing, silver anodised. For work surface with thickness up to 50 mm.

Mounting hole ø 102 mm.

Three sockets, VDE-compliant, 60°, 16 A, contact-protected.

Fixed supply cable 2.5 m with wire end ferrules, plug supplied unattached.

Description Picture Specification Order number

## **EVOline Port DATA**

Aluminium housing, silver anodised. For work surface with thickness up to 50 mm.

Mounting hole ø 102 mm.

Two sockets, VDE-compliant, 60°, 16 A, contact-protected.

Fixed supply cable 3.0 m with angled plug.

Two modular couplings RJ45 to RJ45 CAT 6 shielded,

1:1 interconnected.



rocking cover and collar made of silver lacquered plastic

1593 1003 1400

rocking cover and collar made of black lacquered plastic

1593 1003 1500

rocking cover made of solid stainless steel in CD design, collar made of plastic, lacquered in stainless steel optics

1593 1003 1600

rocking cover made of solid stainless steel in CD design. Collar made of plastic, lacquered in stainless steel optics. NIGHTLIGHT effect by blue LEDs under rocking cover with illuminated ON/OFF switch

1593 1003 1700

#### **EVOline Port DATA**

Aluminium housing, silver anodised. For work surface with thickness up to 50 mm.

Mounting hole ø 102 mm.
Three sockets, VDE-compliant, 60°, 16 A, contact-protected.
Fixed supply cable 3.0 m with angled plug.
Two modular couplings RJ45 to RJ45 CAT 6 shielded,
1:1 interconnected.



rocking cover and collar made of silver lacquered plastic

1593 1003 1800

rocking cover and collar made of black lacquered plastic

1593 1003 1900

rocking cover made of solid stainless steel in CD design, collar made of plastic, lacquered in stainless steel optics

1593 1003 2000

rocking cover made of solid stainless steel in CD design. Collar made of plastic, lacquered in stainless steel optics. NIGHTLIGHT effect by blue LEDs under rocking cover with illuminated ON/OFF switch

1593 1003 2100

Description Picture Specification Order number

## **EVOline Port USB CHARGER\***

Aluminium housing, silver anodised. For work surface with thickness up to 50 mm.

Mounting hole ø 102 mm. Two sockets, VDE-compliant, 60°, 16 A, contact-protected. Fixed supply cable 3.0 m with angled plug.

1x USB Type A Charger, charging function only - ideal for charging of USB-chargeable devices i.e. Apple (iPhones, iPads, iPods,) \*\* Tablets, Smart phones, MP3 Players.



rocking cover and collar made of silver lacquered plastic

rocking cover and collar made of black lacquered plastic

rocking cover made of solid stainless steel in CD design, collar made of plastic. lacquered in stainless steel optics

1593 1040 0200

1593 1040 0300

1593 1040 0400

# EVOline Port USB CHARGER\* Alu-

minium housing, silver anodised. For work surface with thickness up to 50 mm.

Mounting hole ø 102 mm. Three sockets, VDE-compliant, 60°, 16 A, contact-protected. Fixed supply cable 3.0 m with angled plug.

2x USB Type A Charger, charging function only - ideal for charging of USB-chargeable devices i.e. Apple (iPhones, iPads, iPods,) \*\* Tablets, Smart phones, MP3 Players.

The USB charging function cannot be guaranteed due to the multitude of manufacturers and devices on the market

\*\* ™ Apple Computer Inc.



rocking cover and collar made of silver lacquered plastic

rocking cover and collar made of black lacquered plastic

rocking cover made of solid stainless steel in CD design, collar made of plastic, lacquered in stainless steel

1593 1038 7200

1593 1038 4100

1593 1038 7100



Witteveen Projectinrichting Ouderkerk a/d Amstel Tel: 020 - 496 5030 info@witteveen.nl www.project-inrichting.nl www.ergonomics.nl

Become a co-designer and configure your very own EVOline Port. Select from various finishes, illuminations and modules for power, data, multimedia and safety.

Directly to **EVOline** Configurator. www.evoline.com/ konfigurator





